

# AMERICAN MOTORS

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
85	83-87	(1.4L) Alliance	<b>P1496</b> <b>C1496</b>	4	2.992	76.00	4 - 1.75 4 - 2.00	4 - 3.97
105	86-88	(1.7L) Alliance	<b>P1636</b> <b>C1636</b>	4	3.189	81.00	4 - 1.75 4 - 2.00	4 - 3.00
121	77-79	(2.0L)	<b>P1434</b> <b>C1434</b>	4	3.406	86.50	4 - 2.00 4 - 2.50	4 - 5.00
150	83-92	(2.5L)	<b>P2238</b> <b>C2238</b>	4	3.875	98.40	4 - 5/64 4 - 5/64	4 - 3/16
151	80-81	(2.5L)	<b>P3835</b> <b>C3835</b>	4	4.000	101.60	4 - 5/64 4 - 5/64	4 - 3/16
151	82-84	(2.5L)	<b>P3836</b> <b>C3836</b>	4	4.000	101.60	4 - 1/16 4 - 5/64	4 - 3/16
173	84-86	(2.8L) (Shallow Oil Ring Groove)	<b>P3849</b> <b>C3849</b>	6	3.504	89.00	6 - 1.50 6 - 2.00	6 - 4.75
196	57-62	(3.2L) Rambler (With 3/32 Comp. Rings)	<b>P2199</b> <b>C2199</b>	6	3.125	79.37	6 - 3/32 6 - 3/32	6 - 3/16
196	63-65	(3.2L) (With 5/64 Comp. Rings)	<b>P2200</b> <b>C2200</b>	6	3.125	79.37	6 - 5/64 6 - 5/64	6 - 3/16
199	65-70	(3.3L)	<b>P2276</b> <b>C2276</b>	6	3.750	95.25	6 - 5/64 6 - 5/64	6 - 3/16
232	64-79	(3.8L)	<b>P2276</b> <b>C2276</b>	6	3.750	95.25	6 - 5/64 6 - 5/64	6 - 3/16
246	86-92	(4.0L)	<b>P2240</b> <b>C2240</b>	6	3.875	98.40	6 - 5/64 6 - 5/64	6 - 3/16
250	56-62	(4.1L)	<b>P2291</b> <b>C2291</b>	8	3.500	88.90	8 - 5/64 8 - 5/64	8 - 3/16
252	70-72	(4.1L) Rally (Mexico)	<b>P1620</b> <b>C1620</b>	6	3.910	99.30	6 - 5/64 6 - 5/64	6 - 3/16
258	71-85	(4.2L)	<b>P2276</b> <b>C2276</b>	6	3.750	95.25	6 - 5/64 6 - 5/64	6 - 3/16
282	73-86	(4.6L) Classic (Mexico)	<b>P1620</b> <b>C1620</b>	6	3.910	99.30	6 - 5/64 6 - 5/64	6 - 3/16
287	63-66	(4.7L)	<b>P2119</b> <b>C2119</b>	8	3.750	95.25	8 - 5/64 8 - 5/64	8 - 3/16
290	66-69	(4.8L)	<b>P2119</b> <b>C2119</b>	8	3.750	95.25	8 - 5/64 8 - 5/64	8 - 3/16
304	70-79	(5.0L)	<b>P2119</b> <b>C2119</b>	8	3.750	95.25	8 - 5/64 8 - 5/64	8 - 3/16
327	57-66	(5.4L)	<b>P2271</b> <b>C2271</b>	8	4.000	101.60	8 - 5/64 8 - 5/64	8 - 3/16
343	67-69	(5.6L)	<b>P2292</b> <b>C2292</b>	8	4.080	103.60	8 - 5/64 8 - 5/64	8 - 3/16
360	70-79	(5.9L)	<b>P2292</b> <b>C2292</b>	8	4.080	103.60	8 - 5/64 8 - 5/64	8 - 3/16
390	68-70	(6.4L)	<b>P2293</b> <b>C2293</b>	8	4.165	105.79	8 - 5/64 8 - 5/64	8 - 3/16
401	71-76	(6.6L)	<b>P2293</b> <b>C2293</b>	8	4.165	105.79	8 - 5/64 8 - 5/64	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone