

# CHRYSLER

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
85	79-85	(1.4L) Dodge Colt, Plymouth Champ (Mits. eng.) G12B, J	<b>P1417</b> <b>C1417</b>	4	2.913	74.00	4 - 1.50 4 - 1.50	4 - 4.00
91	70-73	(1.5L) Plymouth Cricket	<b>P1332</b> <b>C1332</b>	4	3.391	86.10	4 - 5/64 4 - 5/64	4 - 5/32
92	91-96	(1.5L) Dodge/Plymouth Colt, Eagle Summit 12V 4G15, Q	<b>C1778</b> <sup>+</sup>	4	2.972	75.50	4 - 1.20 4 - 1.50	4 - 3.00
92	85-90	(1.5L) Dodge/Plymouth Colt (Mits. eng.) G15B, Q	<b>P1602</b> <b>C1602</b>	4	2.972	75.50	4 - 1.50 4 - 1.50	4 - 4.00
97	83-88	(1.6L) Dodge Omni, Plymouth Horizon (Peugeot eng.)	<b>P1587</b> <b>C1587</b>	4	3.174	80.62	4 - 1.75 4 - 2.00	4 - 4.00
98	71-84	(1.6L) Dodge, Plymouth (Mits. eng.) G32B, K, Z	<b>P1298</b> <b>C1298</b>	4	3.028	76.90	4 - 2.00 4 - 2.00	4 - 4.00
98	85-88	(1.6L) Dodge/Plymouth Colt (Mits. eng.) G32B	<b>P1604</b> <b>C1604</b>	4	3.028	76.90	4 - 1.50 4 - 1.50	4 - 4.00
98	89-93	(1.6L) Dodge Colt, Eagle Summit (Mits. eng.) G61B, K	<b>C1724</b> <sup>+</sup>	4	3.240	82.30	4 - 1.20 4 - 1.50	4 - 3.00
105	78-83	(1.7L) Dodge Omni, Plymouth (VW eng.) E82	<b>P1429</b> <b>C1429</b>	4	3.130	79.50	4 - 1.75 4 - 2.00	4 - 4.00
107	89-94	(1.8L) Laser G37B, P	<b>P1645</b> <b>C1645</b>	4	3.173	80.60	4 - 1.50 4 - 1.50	4 - 4.00
110	78-88	(1.8L) Dodge/Plymouth Colt (Mits. eng.) G62B	<b>P1527</b> <b>C1527</b>	4	3.173	80.60	4 - 2.00 4 - 2.00	4 - 4.00
110	06-09	(1.8L) Dodge Caliber GEMA 1.8	<b>S5410</b> <sup>+N</sup>	4	3.386	86.00	4 - 1.20 4 - 1.20	4 - 2.00
112	92-94	(1.8L) Dodge/Plymouth Colt/Colt Vista	<b>C3892</b> <sup>+</sup>	4	3.189	81.00	4 - 1.20 4 - 1.20	4 - 2.80
121	95-00	(2.0L) Dodge Stratus C, F	<b>P3896</b> <sup>+</sup>	4	3.445	87.50	4 - 1.20	4 - 3.00
121	95-05	(2.0L) Dodge Neon, L4 C, F	<b>C3896</b> <sup>+</sup>	4	3.445	87.50	4 - 1.20	4 - 3.00
122	72-82	(2.0L) Dodge, Plymouth (Mits. eng.) G52B, U	<b>P1331</b> <b>C1331</b>	4	3.307	84.00	4 - 2.00 4 - 2.00	4 - 4.00
122	89-92	(2.0L) Eagle (N.A. & Turbo) G63B	<b>C1775</b> <sup>+</sup>	4	3.346	85.00	4 - 1.20	4 - 3.00
122	90-91	(2.0L) Eagle (N.A. & Turbo) G63B		4	3.346	85.00	4 - 1.50	4 - 3.00
122	95-98	(2.0L) 4G63	<b>C1951</b> <sup>+</sup>	4	3.346	85.00	4 - 1.20 4 - 1.50	4 - 2.80
122	83-86	(2.0L) Dodge, Plymouth (Mits. eng.) G63B, A	<b>P1528</b> <b>C1528</b>	4	3.346	85.00	4 - 2.00 4 - 2.00	4 - 4.00
122	07-15	(2.0L) Jeep Patriot GEMA 2.0	<b>S5410</b> <sup>+N</sup>	4	3.386	86.00	4 - 1.20	4 - 2.00
122	06-12	(2.0L) Dodge Caliber GEMA 2.0		4	3.386	86.00	4 - 1.20	4 - 2.00
122	07-15	(2.0L) Jeep Compass GEMA 2.0		4	3.386	86.00	4 - 1.20	4 - 2.00
135	85-93	(2.2L) Dodge/Plymouth (Turbo)	<b>C1714</b> <sup>+</sup>	4	3.445	87.50	4 - 1.50	4 - 4.00
135	82-93	(2.2L) Chrysler (Turbo)		4	3.445	87.50	4 - 1.50	4 - 4.00
135	92-97	(2.2L) Chrysler (Turbo), 16V	<b>C3893</b> <sup>+</sup>	4	3.445	87.50	4 - 1.50 4 - 1.50	4 - 3.00
135	81-89	(2.2L) Plymouth Reliant	<b>P1486</b>	4	3.445	87.50	4 - 1.50	4 - 4.00
135	81-85	(2.2L) Dodge Aries	<b>C1486</b>	4	3.445	87.50	4 - 1.50	4 - 4.00
135	84-88	(2.2L) Chrysler LeBaron E62		4	3.445	87.50	4 - 1.50	4 - 4.00
135	82-95	(2.2L) Dodge (Shallow Oil Ring Groove)	<b>P1830</b>	4	3.445	87.50	4 - 1.50	4 - 4.00
135	85-95	(2.2L) Chrysler (Shallow Oil Ring Groove)	<b>C1830</b>	4	3.445	87.50	4 - 1.50	4 - 4.00
143	83-86	(2.3L) Dodge D-50 Pickup, Plymouth Ram 50 (Mits. eng.) (Diesel) 4D55, D	<b>C1530</b> <sup>+</sup>	4	3.587	91.10	4 - 2.50 <sup>HK</sup> 4 - 2.00 <sup>HK</sup>	4 - 4.00
144	07-15	(2.4L) Jeep Patriot GEMA 2.4	<b>S5335</b> <sup>+N</sup>	4	3.465	88.00	4 - 1.20	4 - 2.00
144	07-10	(2.4L) Chrysler Sebring GEMA 2.4		4	3.465	88.00	4 - 1.20	4 - 2.00
144	07-15	(2.4L) Dodge Avenger GEMA 2.4		4	3.465	88.00	4 - 1.20	4 - 2.00
144	09-15	(2.4L) Dodge Journey GEMA 2.4		4	3.465	88.00	4 - 1.20	4 - 2.00

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

# CHRYSLER

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
144	06-12	(2.4L) Dodge Caliber GEMA 2.4						
144	07-15	(2.4L) Jeep Compass GEMA 2.4						
144	11-14	(2.4L) Chrysler 200 GEMA 2.4						
146	01-06	(2.4L) Dodge Stratus (Mits. eng.) 4G64	<b>C1883</b> <sup>+</sup>	4	3.406	86.50	4 - 1.20	4 - 2.80
146	93-96	(2.4L) Dodge Colt Vista, Eagle Summit (Mits. eng.) 4G64					4 - 1.50	
146	01-08	(2.4L) Chrysler Sebring (Mits. eng.) 4G64						
146	90-93	(2.4L) Dodge RAM 50 (Mits. eng.) 4G64	<b>P1652</b>	4	3.406	86.50	4 - 1.50	4 - 4.00
146	1992	(2.4L) Eagle Summit (Mits. eng.) G64B	<b>C1652</b>				4 - 1.50	
146	90-92	(2.4L) Dodge Colt Vista (Mits. eng.) 4G64						
146	05-06	(2.4L) Dodge SRT-4 EDT 2.4, E	<b>S3959</b> <sup>+</sup>	4	3.445	87.50	4 - 1.20	4 - 2.50
146	03-06	(2.4L) Dodge Neon EDT 2.4, E					4 - 1.50	
146	03-10	(2.4L) Chrysler PT Cruiser EDT 2.4, E						
146	93-05	(2.4L) Mitsubishi RDS2 4G64	<b>C3968</b> <sup>+</sup>	4	3.465	88.00	4 - 1.20	4 - 2.00
							4 - 1.20	
148	98-05	(2.4L) Incl. Turbo B, G, X, 1	<b>C3918</b> <sup>+</sup>	4	3.445	87.50	4 - 1.20	4 - 3.00
148	98-01	(2.4L) Dodge Stratus B, G, X, 1					4 - 1.50	
148	98-00	(2.4L) Dodge Caravan B, G, X, 1						
148	03-08	(2.4L) Chrysler PT Cruiser	<b>P3897</b>	4	3.445	87.50	4 - 1.50	4 - 3.00
148	96-97	(2.4L) Chrysler Sebring, Dodge Caravan, Grand Caravan, Plymouth Breeze, Grand Voyager	<b>C3897</b>				4 - 1.50	
148	03-06	(2.4L) Chrysler Sebring, Dodge Stratus						
148	01-04	(2.4L) Dodge Caravan, Plymouth Voyager						
148	95-97	(2.4L) Dodge Stratus, Plymouth Cirrus						
148	2002	(2.4L) Chrysler PT Cruiser, Sebring, Dodge Stratus						
152	95-00	(2.5L) Chrysler Cirrus 6G73	<b>C5004</b> <sup>+</sup>	6	3.287	83.50	6 - 1.20	6 - 3.00
152	95-00	(2.5L) Avenger, Cirrus, Sebring, Stratus 6G73					6 - 1.50	
153	86-95	(2.5L) Chrysler (Turbo) (Shallow Oil Ring Groove)	<b>C3885</b> <sup>+</sup>	4	3.445	87.50	4 - 1.50	4 - 4.00
							4 - 1.50	
153	94-97	(2.5L) Chrysler (Turbo) (Shallow Oil Ring Groove)	<b>C3922</b> <sup>+</sup>	4	3.445	87.50	4 - 1.50	4 - 4.00
							4 - 1.50	
153	86-89	(2.5L) Dodge, Plymouth	<b>P1486</b> <b>C1486</b>	4	3.445	87.50	4 - 1.50	4 - 4.00
							4 - 1.50	
153	82-93	(2.5L) Eagle Premier (Turbo)	<b>P2238</b> <b>C2238</b>	4	3.875	98.40	4 - 5/64	4 - 3/16
							4 - 5/64	
153	96-99	(2.5L) Dodge L4	<b>P3926</b> <b>C3926</b>	4	3.875	98.40	4 - 1.50	4 - 4.00
							4 - 1.50	
155	82-84	(2.6L) Chrysler LeBaron, New Yorker (Mits. eng.) G54B	<b>P1438</b> <b>C1438</b>	4	3.587	91.10	4 - 2.00	4 - 4.00
							4 - 2.00	
156	77-83	(2.5L) Chrysler, Dodge, Plymouth (Mits. eng.) G54B	<b>P1438</b> <b>C1438</b>	4	3.587	91.10	4 - 2.00	4 - 4.00
							4 - 2.00	
156	83-89	(2.6L) Chrysler, Dodge, Plymouth (Mits. eng.) G54B	<b>P1529</b>	4	3.587	91.10	4 - 1.50	4 - 4.00
156	1985	(2.6L) Chrysler LeBaron, New Yorker (Mits. eng.) G54B	<b>C1529</b>				4 - 1.50	
167	98-03	(2.7L) 2700 Vin: R, T, U	<b>S3974</b> <sup>+N</sup>	6	3.386	86.00	6 - 1.50	6 - 3.00
							6 - 1.50	
167	98-05	(2.7L) Chrysler Concorde, Dodge Intrepid	<b>P3925</b> <b>C3925</b>	6	3.386	86.00	6 - 1.50	6 - 3.00
							6 - 1.50	
170	60-69	(2.8L) Dodge, Plymouth	<b>P2128</b> <b>C2128</b>	6	3.400	86.36	6 - 5/64	6 - 3/16
							6 - 5/64	
181	91-95	(3.0L) Chrysler (N.A. & Turbo) V	<b>C3878</b>	6	3.587	91.10	6 - 1.20	6 - 3.00
							6 - 1.50	
181	87-93	(3.0L) Dodge Dynasty LE, Plymouth Caravan, 12V (Mits. eng.) G72B	<b>P1664</b> <b>C1664</b>	6	3.587	91.10	6 - 1.50	6 - 4.00
							6 - 1.50	

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

# CHRYSLER

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
182	90-91	(3.0L) Dodge Monaco (Renault eng.)	<b>P1774<sup>A</sup></b> <b>C1774<sup>A</sup></b>	6	3.661	93.00	6 - 1.75 6 - 1.75	6 - 3.50
197	98-01	(3.2L) Chrysler Concorde, Dodge Intrepid J	<b>C3923<sup>+</sup></b>	6	3.622	92.00	6 - 1.20 6 - 1.50	6 - 3.00
198	70-74	(3.2L) Dodge, Plymouth	<b>P2128</b> <b>C2128</b>	6	3.400	86.36	6 - 5/64 6 - 5/64	6 - 3/16
201	88-97	(3.3L) Dodge, Plymouth	<b>P3877</b> <b>C3877</b>	6	3.661	93.00	6 - 1.50 6 - 1.50	6 - 3.00
201	98-05	(3.3L) Chrysler (Shallow Oil Ring Groove) G, R, 3	<b>P3924</b> <b>C3924</b>	6	3.661	93.00	6 - 1.50 6 - 1.50	6 - 3.00
215	96-10	(3.5L) Chrysler F, G, K, V	<b>C3887<sup>+</sup></b>	6	3.780	96.00	6 - 1.20 6 - 1.50	6 - 3.00
215	1997	(3.5L) Plymouth Prowler F, G, K, V						
215	95-97	(3.5L) Chrysler Concorde, Dodge Intrepid, Chrysler LHS, Eagle Vision F, G, K, V						
215	95-96	(3.5L) Chrysler New Yorker F, G, K, V						
218	42-59	(3.6L) Dodge, Plymouth	<b>P2124</b> <b>C2124</b>	6	3.250	82.55	6 - 3/32 6 - 3/32	6 - 5/32 6 - 5/32
218	35-40	(3.6L) Dodge	<b>P2130</b> <b>C2130</b>	6	3.250	82.55	6 - 1/8 6 - 1/8	6 - 5/32 6 - 5/32
225	60-87	(3.7L) Dodge, Plymouth	<b>P2128</b>	6	3.400	86.36	6 - 5/64 6 - 5/64	6 - 3/16
225	76-85	(3.7L) Chrysler	<b>C2128</b>					
228	35-41	(3.8L) Desoto	<b>P2140</b>	6	3.375	85.70	6 - 1/8 6 - 1/8	6 - 5/32 6 - 5/32
228	38-41	(3.8L) Chrysler	<b>C2140</b>					
230	42-59	(3.8L) Dodge, Plymouth	<b>P2124</b> <b>C2124</b>	6	3.250	82.55	6 - 3/32 6 - 3/32	6 - 5/32 6 - 5/32
231	91-02	(3.8L) Dodge, Plymouth L, 6	<b>P3874</b> <b>C3874</b>	6	3.780	96.00	6 - 1.50 6 - 1.50	6 - 3.00
237	42-51	(3.9L) Desoto	<b>P2142</b>	6	3.437	87.30	6 - 3/32 6 - 3/32	6 - 5/32 6 - 5/32
237	42-54	(3.9L) Dodge Canada	<b>C2142</b>					
239	87-91	(3.9L) Dodge, Plymouth	<b>P1620</b> <b>C1620</b>	6	3.910	99.30	6 - 5/64 6 - 5/64	6 - 3/16
239	92-03	(3.9L) Dodge Truck	<b>P3912</b> <b>C3912</b>	6	3.910	99.30	6 - 2.00 6 - 2.00	6 - 4.00
241	53-55	(3.9L) Dodge, Plymouth	<b>P2132</b> <b>C2132</b>	8	3.437	87.30	8 - 5/64 8 - 5/64	8 - 3/16
251	55-68	(4.1L) Dodge Truck	<b>P2134</b> <b>C2134</b>	6	3.437	87.30	6 - 5/64 6 - 5/64	6 - 3/16
251	49-51	(4.1L) Desoto	<b>P2142</b>	6	3.437	87.30	6 - 3/32 6 - 3/32	6 - 5/32 6 - 5/32
251	42-52	(4.1L) Chrysler	<b>C2142</b>					
259	55-56	(4.2L) Dodge	<b>P2186</b>	8	3.563	90.50	8 - 5/64 8 - 5/64	8 - 3/16
259	1955	(4.1L) Plymouth K	<b>C2186</b>					
265	55-68	(4.3L) Dodge Truck	<b>P2134</b> <b>C2134</b>	6	3.437	87.30	6 - 5/64 6 - 5/64	6 - 3/16
265	51-54	(4.3L) Exc. Canada	<b>P2142</b>	6	3.437	87.30	6 - 3/32 6 - 3/32	6 - 5/32 6 - 5/32
265	42-51	(4.3L) Desoto	<b>C2142</b>					
270	55-56	(4.4L) Dodge, Plymouth	<b>P2145</b> <b>C2145</b>	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
273	64-69	(4.5L) Dodge, Plymouth	<b>P2145</b> <b>C2145</b>	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
276	52-54	(4.5L) Desoto	<b>P2145</b> <b>C2145</b>	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
277	56-57	(4.5L) Plymouth	<b>P2119</b> <b>C2119</b>	8	3.750	95.25	8 - 5/64 8 - 5/64	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

# CHRYSLER

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
287	99-07	(4.7L) Dodge Truck N	<b>P3927</b> <b>C3927</b>	8	3.661	93.00	8 - 1.50 8 - 1.50	8 - 3.00
290	55-56	(4.7L) Desoto	<b>P2146</b> <b>C2146</b>	8	3.720	94.50	8 - 5/64 8 - 5/64	8 - 3/16
301	1955	(4.9L) Chrysler	<b>P2145</b> <b>C2145</b>	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
301	1957	(4.9L) Plymouth	<b>P2127</b> <b>C2127</b>	8	3.910	99.30	8 - 5/64 8 - 5/64	8 - 3/16
303	54-56	(5.0L) Dodge	<b>P2339</b> <b>C2339</b>	8	3.813	96.85	8 - 5/64 8 - 5/64	8 - 3/16
315	1956	(5.2L) Dodge	<b>P2145</b> <b>C2145</b>	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
318	60-93	(5.2L) Dodge	<b>P2127</b>	8	3.910	99.30	8 - 5/64	8 - 3/16
318	58-89	(5.2L) Plymouth	<b>C2127</b>				8 - 5/64	
318	75-89	(5.2L) Chrysler						
318	91-03	(5.2L) Dodge Truck (Shallow Oil Ring Groove)	<b>P3911</b> <b>C3911</b>	8	3.910	99.30	8 - 2.00 8 - 2.00	8 - 4.00
324	42-50	(5.4L) Chrysler C30, C36, IND9, IND12	<b>P2143</b>	8	3.250	82.55	8 - 3/32 8 - 3/32	8 - 5/32 8 - 5/32
325	1957	(5.3L) Desoto	<b>P2148</b>	8	3.688	93.67	8 - 5/64	8 - 3/16
325	57-58	(5.3L) Dodge	<b>C2148</b>				8 - 5/64	
330	55-56	(5.4L) Desoto	<b>P2146</b> <b>C2146</b>	8	3.720	94.50	8 - 5/64 8 - 5/64	8 - 3/16
331	51-56	(5.5L) Chrysler	<b>P2339</b>	8	3.813	96.85	8 - 5/64	8 - 3/16
331	54-56	(5.5L) Dodge	<b>C2339</b>				8 - 5/64	
331	1956	(5.5L) Plymouth						
340	68-73	(5.6L) Dodge, Plymouth	<b>P2277</b> <b>C2277</b>	8	4.040	102.61	8 - 5/64 8 - 5/64	8 - 3/16
341	1957	(5.6L) Desoto	<b>P2149</b> <b>C2149</b>	8	3.780	96.00	8 - 5/64 8 - 5/64	8 - 3/16
345	10-15	(5.7L) Dodge Durango Hemi 5.7	<b>S3982<sup>N</sup></b>	8	3.917	99.50	8 - 1.20	8 - 2.00
345	10-15	(5.7L) Chrysler 300 EZB Hemi 5.7					8 - 1.20	
345	09-15	(5.7L) Dodge Challenger Hemi 5.7						
345	10-15	(5.7L) Dodge Charger Hemi 5.7						
348	03-08	(5.7L) Hemi Vin: D, H, 2	<b>P3975<sup>+N</sup></b> <b>C3975<sup>+N</sup></b>	8	3.917	99.50	8 - 1.50 8 - 1.50	8 - 3.00
350	1958	(5.7L) Desoto, Dodge, Plymouth	<b>P2135</b> <b>C2135</b>	8	4.063	103.19	8 - 5/64 8 - 5/64	8 - 3/16
354	56-58	(5.8L) Chrysler	<b>P3158</b>	8	3.937	100.00	8 - 5/64	8 - 3/16
354	56-59	(5.8L) Dodge	<b>C3158</b>				8 - 5/64	
360	71-80	(5.9L) Plymouth	<b>P2271</b>	8	4.000	101.60	8 - 5/64	8 - 3/16
360	71-95	(5.9L) Dodge	<b>C2271</b>				8 - 5/64	
360	71-84	(5.9L) Chrysler						
360	93-04	(5.9L) Dodge Truck Z	<b>P3915</b> <b>C3915</b>	8	4.000	101.60	8 - 1.50 8 - 1.50	8 - 4.00
361	59-69	(5.9L) Canada	<b>P2187</b>	8	4.125	104.78	8 - 5/64	8 - 3/16
361	58-61	(5.9L) Desoto	<b>C2187</b>				8 - 5/64	
361	58-66	(5.9L) Dodge, Plymouth						
361	60-76	(5.9L) Dodge Truck	<b>P2995</b> <b>C2995</b>	8	4.125	104.78	8 - 3/32 8 - 3/32	8 - 3/16
383	59-71	(6.3L) Dodge, Plymouth	<b>P2378</b>	8	4.250	107.95	8 - 5/64	8 - 3/16
383	59-61	(6.3L) Desoto	<b>C2378</b>				8 - 5/64	
392	56-58	(6.4L)	<b>P2271</b> <b>C2271</b>	8	4.000	101.60	8 - 5/64 8 - 5/64	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

# CHRYSLER

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
400	72-78	(6.6L) Chrysler, Dodge, Plymouth	<b>P3809</b> <b>C3809</b>	8	4.342	110.28	8 - 5/64 8 - 5/64	8 - 3/16
413	59-66	(6.8L)	<b>P2377</b>	8	4.188	106.36	8 - 5/64	8 - 3/16
413	63-65	(6.8L) Dodge	<b>C2377</b>				8 - 5/64	
413	60-78	(6.8L) Dodge Truck	<b>P2448</b> <b>C2448</b>	8	4.188	106.36	8 - 3/32 8 - 3/32	8 - 3/16
426	63-71	(7.0L) Dodge, Plymouth	<b>P2378</b> <b>C2378</b>	8	4.250	107.95	8 - 5/64 8 - 5/64	8 - 3/16
440	66-80	(7.2L) Dodge	<b>P2382</b>	8	4.320	109.70	8 - 5/64	8 - 3/16
440	66-78	(7.2L) Chrysler, Plymouth	<b>C2382</b>				8 - 5/64	
478	70-78	(7.8L) Dodge	<b>P2498</b> <b>C2498</b>	8	4.500	114.30	8 - 3/32 8 - 3/32	8 - 3/16
488	94-03	(8.0L) Dodge W	<b>P3928</b> <b>C3928</b>	10	4.000	101.60	10 - 1.50 10 - 1.50	10 - 4.00
549	70-78	(9.0L) Dodge	<b>P2498</b> <b>C2498</b>	8	4.500	114.30	8 - 3/32 8 - 3/32	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone