

# CLIMAX

Application	Engine	Cyl	CC	Years	Set Number		Line No
	Model	Bore			Chrome	Plain	
(5-Ring Double Oil)		177.80				P0257	4
(5-Ring Single Oil)		177.80				P0545 <sup>A</sup>	6
C106 (32 H.P.)		190.50				P0544 <sup>A</sup>	7
C46 (10 H.P.)		127.00				P3685 <sup>A</sup>	1
C66 (4-Ring) (14 H.P.)		146.10				P3686 <sup>A</sup>	2
C66 (5-Ring)		146.10				P3687 <sup>A</sup>	3
C96 (4-Ring) (20 H.P.)		177.80				P0542 <sup>A</sup>	5

Line		CC	Set No	Cyl	Bore Diameter		Ring Size	
No	Application				Inch	MM	Comp	Oil
1	C46 (10 H.P.)		P3685 <sup>A</sup>	1	5.000	127.00	1 - 1/4 1 - 1/4 1 - 1/4	1 - 1/4
2	C66 (4-Ring) (14 H.P.)		P3686 <sup>A</sup>	1	5.750	146.10	1 - 1/4 1 - 1/4 1 - 1/4	1 - 1/4
3	C66 (5-Ring)		P3687 <sup>A</sup>	1	5.750	146.10	4 - 1/4	1 - 1/4
4	(5-Ring Double Oil)		P0257	1	7.000	177.80	1 - 1/4 1 - 1/4 1 - 1/4	1 - 1/4
5	C96 (4-Ring) (20 H.P.)		P0542 <sup>A</sup>	1	7.000	177.80	1 - 1/4 1 - 1/4 1 - 1/4	1 - 1/4
6	(5-Ring Single Oil)		P0545 <sup>A</sup>	1	7.000	177.80	3 - 1/4 1 - 1/4	1 - 1/4
7	C106 (32 H.P.)		P0544 <sup>A</sup>	1	7.500	190.50	1 - 1/4 1 - 1/4 1 - 1/4	1 - 1/4

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone